




adapter 0.5X
(included)



calibration rule
(included, graduation 0.01mm)

- For high magnification observation and metallurgical image analysis
- Infinite optical system, can add optical accessories like polarizer, analyzer, DIC (code ISM-M2000-DIC) into optical path without image quality influence
- Objective can be used in both bright field and dark field
- Kohler illumination system provides uniform illumination field
- Three working modes: 100% eyepiece observation, 100% camera observation, both eyepiece and camera observation (80% illuminance for camera and 20% illuminance for eyepiece)

SPECIFICATION

Eyepiece (wide field)	10X (view field: Ø22mm)				
Objective (plan achromatic)	5X (included)	10X (included)	20X (included)	50X (included)	100X (included)
Numerical aperture	0.12	0.25	0.40	0.75	0.90
Working distance	10mm	10mm	5mm	1.3mm	0.7mm
Stage	double layer, size: 160×140mm, travel: 75×50mm (graduation: 0.1mm)				
Kohler illumination	12V/50W halogen lamp, brightness is adjustable with polarizer and analyzer, built-in green, yellow, blue, gray and frosted glass				
Pupil distance	48~75mm				
Diopter adjustment	±5 diopter (two eyepieces)				
Power supply	110/220V, 50/60Hz				
Dimension (L×W×H)	647×268×376mm				
Weight	12kg				

METALLURGICAL MICROSCOPE CODE ISM-M2000



STANDARD DELIVERY

Main unit	1pc
10X dividing eyepiece (0.1mm/div.)	1pc
Calibration rule (graduation 0.01mm)	1pc
Camera adapter	1pc
Adapter 0.5X	1pc
Anti-dust cover	1pc

OPTIONAL ACCESSORY

15X eyepiece (view field: Ø16mm)	ISM-M2000-15X
20X eyepiece (view field: Ø12mm)	ISM-M2000-20X
DIC	ISM-M2000-DIC
Metallurgical image analysis software and camera	ISM-MAS100